

ROPAC® MP 5 LH
UN Certified
for dangerous solid goods
Technical Data Sheet



Schoeller Allibert



PACKAGING DESCRIPTION – RANGE SECURE

| | |
|---|---|
| Commercial reference | ROPAC® MP 5 LH |
| Shape | Conical |
| Packaging type (following ADR) | 1H2 |
| Reference | ADR, RID, ADNR, IMDG-Code, DOC OACI 9284 AN 905 |
| External diameter at top | 217 mm |
| Height incl. lid | 219 mm |
| Closing system | Press-on lid with tear-off band |
| Oxygen permeability (following ASTM D 3985) | 0,70 cm ³ /day for 21% oxygen |
| UN certified for | II and III (group b and c of each class, excepted 1 and 2). |
| Packaging classification | Dangerous solid goods |
| Handling | Plastic handle |
| Raw material | HDPE |
| Stackability | UN load: 79kg/24h/23°C |
| Option | Flex-spout on request |



PAIL CHARACTERISTICS – REFERENCE 7505006

| | |
|--|------------------------------------|
| Volume brim full | 5,9 l (1.56 US gallon) |
| Volume under lid | 5,5 l (1.45 US gallon) |
| UN certified for a maximum weight of content | 6 kg |
| Weight | 298 g (handle +14 g) |
| External diameter at bottom | 179,6 mm |
| Embossing | Ⓜ 1H2/Y6/S/--/F/BVT260829 |
| Decoration type | Digital print |
| Decoration area | On request |
| Standard palletisation (800x1200 NIMP15) | 540 pieces (18 piles of 30 pieces) |
| Height of pallet | 1,91 m |



LID CHARACTERISTICS – REFERENCE 7536030

| | |
|--|---|
| Weight | 91 g (gasket + 4 g) |
| External diameter | 213 mm |
| Embossing | Ⓜ MP3-6 H |
| Gasket | SEBS |
| Standard palletisation (800x1200 NIMP15) | 1620 pieces with or without flex-spout (6 boxes of 270 pcs) |
| Height of pallet | 2,02 m |



These specifications are without legal warranty and subject to changes without notification.

November 2023 /SV

SCHOELLER ALLIBERT SWISS Sàrl
 11, route de la Condémine
 CH-1680 ROMONT
 Tel. +41 26 651 92 11
Info.switzerland@schoellerallibert.com
www.ropac-packaging.com

Note: For pharma or food application the pails should be washed before use. The customer has to check the integrity of the packaging, handling-unit aspect and pail deformation due to transport; these risks should be taken into account by the customer in his risks assessment.