

**ROPAC® MP 3 LH**  
**UN Certified**  
**for dangerous solid goods**  
**Technical Data Sheet**



Schoeller Allibert



**PACKAGING DESCRIPTION – RANGE SECURE**

Commercial reference	ROPAC® MP 3 LH
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADNR, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	220,5 mm
Height incl. lid	143 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	0,53 cm <sup>3</sup> /day for 21% oxygen
UN certified for	II and III (group b and c of each class, excepted 1 and 2).
Packaging classification	Dangerous solid goods
Handling	Plastic handle
Raw material	HDPE
Stackability	UN load: 81 kg/24 h/23°C
Option	---



**PAIL CHARACTERISTICS – REFERENCE 7503006**

Volume brim full	3,7 l (0.97 US gallon)
Volume under lid	3,4 l (0.89 US gallon)
UN certified for a maximum weight of content	4 kg
Weight	182 g (handle +14 g)
External diameter at bottom	178 mm
Embossing	Ⓜ 1H2/Y4/S/--/F/BVT/26084
Decoration type	---
Decoration area	---
Standard palletisation (800x1200 NIMP15)	736 pieces (16 piles of 46 pails)
Height of pallet	1,81 m




**LID CHARACTERISTICS – REFERENCE 7536030**

Weight	91 g (gasket + 4 g)
External diameter	216 mm
Embossing	Ⓜ MP 3-6H
Gasket	SEBS
Standard palletisation (800x1200 NIMP15)	1620 pieces (6 boxes of 270 pcs)
Height of pallet	2,02 m



*These specifications are without legal warranty and subject to changes without notification.*

November 2023/SV



SCHOELLER ALLIBERT SWISS Sàrl  
 11, route de la Condémine  
 CH-1680 ROMONT  
 Tel. +41 26 651 92 11  
[Info.switzerland@schoellerallibert.com](mailto:Info.switzerland@schoellerallibert.com)  
[www.ropac-packaging.com](http://www.ropac-packaging.com)

*Note: For pharma or food application the pails should be washed before use. The customer has to check the integrity of the packaging, handling-unit aspect and pail deformation due to transport; these risks should be taken into account by the customer in his risks assessment.*