

ROPAC® MP 10 LH
UN Certified
for dangerous solid goods



Schoeller Allibert



Technical Data Sheet

PACKAGING DESCRIPTION – RANGE SECURE

| | |
|--------------------------------|---|
| Commercial reference | ROPAC® MP 10 LH |
| Shape | Conical |
| Packaging type (following ADR) | 1H2 |
| Reference | ADR, RID, ADN, IMDG-Code, DOC OACI 9284 AN 905 |
| External diameter at top | 268 mm |
| Height incl. lid | 274 mm |
| Closing system | Press-on lid with tear-off band |
| UN certified for | II and III (group b and c of each class, excepted 1 and 2). |
| Packaging classification | Dangerous solid goods |
| Handling | Plastic handle |
| Raw material | HDPE |
| Stackability | UN load : 140 kg/ 24 h/23°C |
| Option | --- |



PAIL CHARACTERISTICS – REFERENCE 7510006

| | |
|--|----------------------------------|
| Volume brim full | 12,0 l (3.17 US gallons) |
| Volume under lid | 11,3 l (2.98 US gallons) |
| UN certified for a maximum weight of content | 14 kg |
| Weight | 475 gr (handle +17 g) |
| External diameter at bottom | 231,8 mm |
| Embossing | Ⓜ 1H2/Y14/S/--/F/BVT 26086 |
| Decoration type | Digital print |
| Decoration area | On request |
| Standard palletisation (800x1200 NIMP15) | 264 pails (12 piles of 22 pails) |
| Height of pallet | 1,87 m |



LID CHARACTERISTICS – REFERENCE 7538020

| | |
|--|---------------------------------|
| Weight | 135 g (gasket + 12 g) |
| External diameter | 266 mm |
| Embossing | Ⓜ MP-10H |
| Gasket | PVC |
| Standard palletisation (800x1200 NIMP15) | 1056 lids (12 piles of 88 lids) |
| Height of pallet | 1,75 m |



These specifications are without legal warranty and subject to changes without notification.

November 2023/SV



SCHOELLER ALLIBERT SWISS Sàrl
 11, route de la Condémine
 CH-1680 ROMONT
 Tel. +41 26 651 92 11
Info.switzerland@schoellerallibert.com
www.ropac-packaging.com

Note: For pharma or food application the pails should be washed before use. The customer has to check the integrity of the packaging, handling-unit aspect and pail deformation due to transport; these risks should be taken into account by the customer in his risks assessment.