

**ROPAC® MP 15 LH**  
**UN Certified**  
**for dangerous solid goods**



Schoeller Allibert



**Technical Data Sheet**

**PACKAGING DESCRIPTION – RANGE SECURE**

Commercial reference	ROPAC® MP 15 LH
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADN, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	320 mm
Height incl. lid	286,5 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	1,38 cm <sup>3</sup> / day for 21% oxygen
UN certified for	Dangerous solid goods
Packaging classification	II and III (group b and c of each class, excepted 1 and 2).
Handling	Plastic handle
Raw material	HDPE
Stackability	UN load: 224 kg / 24 h /23°C
Option	Flex-spout on request



**PAIL CHARACTERISTICS – REFERENCE 7515006**

Volume brim full	17,9 l (4.73 US gallons)
Volume under lid	16,4 l (4.33 US gallons)
UN certified for a maximum weight of content	23 kg
Weight	690 g (handle +27 g)
External diameter at bottom	279 mm
Embossing	Ⓜ 1H2/Y23/S/--/F/BVT 26088/
Decoration type	Digital print
Decoration area	On request
Standard palletisation (800x1200 NIMP15)	160 pails (8 piles of 20 pails)
Height of pallet	1,78 m



**LID CHARACTERISTICS – REFERENCE 7542031**

Weight	220 g (gasket + 17 g)
External diameter	317 mm
Embossing	Ⓜ MP 15-20H
Gasket	SEBS
Standard palletisation (800x1200 NIMP15)	480 lids (8 piles of 60 lids)
Height of pallet	1,67 m



*These specifications are without legal warranty and subject to changes without notification.*

November 2023/SV



SCHOELLER ALLIBERT SWISS Sàrl  
 11, route de la Condémine  
 CH-1680 ROMONT  
 Tel. +41 26 651 92 11  
[Info.switzerland@schoellerallibert.com](mailto:Info.switzerland@schoellerallibert.com)  
[www.ropac-packaging.com](http://www.ropac-packaging.com)

*Note: For pharma or food application the pails should be washed before use. The customer has to check the integrity of the packaging, handling-unit aspect and pail deformation due to transport; these risks should be taken into account by the customer in his risks assessment.*