

ROPAC® MP 31 LH
UN Certified
for dangerous solid goods



Schoeller Allibert



Technical Data Sheet

PACKAGING DESCRIPTION – RANGE SECURE

Commercial reference	ROPAC® MP 31 LH
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADN, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	398 mm
Height incl. lid	372 mm
Closing system	Press-on lid with tear-off band
UN certified for	II and III (group b and c of each class, excepted 1 and 2).
Packaging classification	Dangerous solid goods
Handling	Hand grips
Raw material	HDPE
Stackability	UN load: 293 kg/24h/23°C
Option	Flex-spout on lid



PAIL CHARACTERISTICS – REFERENCE 7525006

Volume brim full	35,2 l (9.30 US gallons)
Volume under lid	32.5 l (8.59 US gallons)
UN certified for a maximum weight of content	40 kg
Weight	1400 g
External diameter at bottom	345 mm
Embossing	Ⓜ 1H2/Y40/S/--/F/BVT 260810/
Decoration type	---
Decoration area	---
Standard palletisation (800x1200 NIMP15)	60 pails (6 piles of 10 pails)
Height of pallet	2,07 m




LID CHARACTERISTICS – REFERENCE 755020

Weight	465 g (gasket + 46 g)
External diameter	392 mm
Embossing	Ⓜ MP 26-31 H
Gasket	PVC
Standard palletisation (800x1200 NIMP15)	300 lids (6 piles of 60 lids)
Height of pallet	1,64 m



These specifications are without legal warranty and subject to changes without notification.

November 2023/SV



SCHOELLER ALLIBERT SWISS Sàrl
 11, route de la Condémine
 CH-1680 ROMONT
 Tel. +41 26 651 92 11
Info.switzerland@schoellerallibert.com
www.ropac-packaging.com

Note: For pharma or food application the pails should be washed before use. The customer has to check the integrity of the packaging, handling-unit aspect and pail deformation due to transport; these risks should be taken into account by the customer in his risks assessment.