

**ROPAC® 10 LL**  
**UN Certified**  
**for dangerous liquid goods**



Schoeller Allibert



**Technical Data Sheet**

**PACKAGING DESCRIPTION – RANGE PRIME**

Commercial reference	ROPAC® 10 LL
Shape	Cylindrical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADN, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	289 mm
Height incl. lid	282 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	0.99 cm <sup>3</sup> /24 <sup>00</sup> for 21% oxygen
Inner pressure resistance	100 kPa during 30 minutes
UN certified for	II and III for liquids 1.6 / III for liquids 2.4
Packaging classification	Dangerous liquid goods Y.16 & Z 2.4
Handling	Plastic handle
Raw material	HDPE
Stackability	Y 195 kg & Z 280 kg (28 days at 40°C)
Option	Flex-spout on request



**PAIL CHARACTERISTICS – REFERENCE 7564006**

Volume brim full	13,6 l (3.59 US gallons)
Volume under lid	12 l (3.17 US gallons)
UN certified for a maximum weight of content	Y 1.6 g/cm <sup>3</sup> and Z 2.4 g/cm <sup>3</sup>
Weight	629 g (handle +17 g)
External diameter at bottom	246 mm
Embossing	Ⓜ 1H2 /Y 1.6 - Z 2.4 /100 /-- /F/ BVT260840
Decoration type	Digital print
Decoration area	On request
Standard palletisation (800x1200 NIMP15)	154 pails (11 piles of 14 pails)
Height of pallet	1,80 m



**LID CHARACTERISTICS – REFERENCE 7584010**

Weight	284 g (gasket + 11 g)
External diameter	279 mm
Embossing	Ⓜ ROPAC 10-20 HLIQ
Gasket	PUR
Standard palletisation (800x1200 NIMP15)	484 lids (11 piles of 44 lids)
Height of pallet	1,60m



*These specifications are without legal warranty and subject to changes without notification.*

November 2023/SV



SCHOELLER ALLIBERT SWISS Sàrl  
 11, route de la Condémine  
 CH-1680 ROMONT  
 Tel. +41 26 651 92 11  
[Info.switzerland@schoellerallibert.com](mailto:Info.switzerland@schoellerallibert.com)  
[www.ropac-packaging.com](http://www.ropac-packaging.com)

*Note: The customer has to check the integrity of the packaging, handling-unit aspect and pail deformation due to transport; these risks should be taken into account by the customer in his risks assessment.*