

ROPAC® MP 5 LH
UN Certified
for dangerous solid goods
Technical Data Sheet



Schoeller Allibert



PACKAGING DESCRIPTION – RANGE SECURE FOOD

Commercial reference	ROPAC® MP 5 LH
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADNR, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	217 mm
Height incl. lid	219 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	0,70 cm ³ /day for 21% oxygen
UN certified for	II and III (group b and c of each class, excepted 1 and 2).
Packaging classification	Dangerous solid goods
Handling	Plastic handle
Raw material	HDPE
Stackability	UN load: 79kg/24h/23°C
Option	Flex-spout on request



PAIL CHARACTERISTICS – REFERENCE 7505206

Volume brim full	5,9 l (1.56 US gallon)
Volume under lid	5,5 l (1.45 US gallon)
UN certified for a maximum weight of content	6 kg
Weight	298 g (handle + 14 g)
External diameter at bottom	179,6 mm
Embossing	Ⓜ 1H2/Y6/S/--/F/BVT260829/
Decoration type	Digital print
Decoration area	On request
Standard palletisation (800x1200 NIMP15)	540 pieces (18 piles of 30 pieces)
Height of pallet	1,91 m



LID CHARACTERISTICS – REFERENCE 7536230

Weight	91 g (gasket + 4 g)
External diameter	213 mm
Embossing	Ⓜ MP3-6 H
Gasket	SEBS
Standard palletisation (800x1200 NIMP15)	1620 pieces with or without flex-spout (6 boxes of 270 pcs)
Height of pallet	2,02 m



*These specifications are without legal warranty and subject to changes without notification.
 November 2023/SV*



SCHOELLER ALLIBERT SWISS Sàrl
 11, route de la Condémine
 CH-1680 ROMONT
 Tel. +41 26 651 92 11
Info.switzerland@schoellerallibert.com
www.ropac-packaging.com

Note: For pharma or food application the pails should be washed before use. The customer has to check the integrity of the packaging, handling-unit aspect and pail deformation due to transport; these risks should be taken into account by the customer in his risks assessment.