

**ROPAC® MP 31 LH**  
**UN Certified**  
**for dangerous solid goods**



Schoeller Allibert



**Technical Data Sheet**

**PACKAGING DESCRIPTION – RANGE SECURE FOOD**

|                                |   |
|--------------------------------|---|
| Commercial reference           | ROPAC® MP 31 LH   |
| Shape                          | Conical   |
| Packaging type (following ADR) | 1H2   |
| Reference                      | ADR, RID, ADN, IMDG-Code, DOC OACI 9284 AN 905              |
| External diameter at top       | 398 mm  |
| Height incl. lid               | 372 mm  |
| Closing system                 | Press-on lid with tear-off band                             |
| UN certified for               | II and III (group b and c of each class, excepted 1 and 2). |
| Packaging classification       | Dangerous solid goods                                       |
| Handling                       | Hand grips  |
| Raw material                   | HDPE  |
| Stackability                   | UN load: 293 kg/24h/23°C                                    |
| Option                         | Flex-spout on lid   |



**PAIL CHARACTERISTICS – REFERENCE 7525206**

|  |                                |
|--|--------------------------------|
| Volume brim full                             | 35,2 l (9.30 US gallons)       |
| Volume under lid                             | 32.5 l (8.59 US gallons)       |
| UN certified for a maximum weight of content | 40 kg                          |
| Weight                                       | 1400 g                         |
| External diameter at bottom                  | 345 mm                         |
| Embossing                                    | Ⓜ 1H2/Y40/S/--/F/BVT 260810/   |
| Decoration type                              | ---                            |
| Decoration area                              | ---                            |
| Standard palletisation (800x1200 NIMP15)     | 60 pails (6 piles of 10 pails) |
| Height of pallet                             | 2,07 m                         |




**LID CHARACTERISTICS – REFERENCE 755032**

|  |                               |
|--|-------------------------------|
| Weight                                   | 465 g (gasket + 48 g)         |
| External diameter                        | 392 mm                        |
| Embossing                                | Ⓜ MP 26-31 H                  |
| Gasket                                   | SEBS                          |
| Standard palletisation (800x1200 NIMP15) | 300 lids (6 piles of 60 lids) |
| Height of pallet                         | 1,64 m                        |



*These specifications are without legal warranty and subject to changes without notification.*

November 2023/SV



SCHOELLER ALLIBERT SWISS Sàrl  
 11, route de la Condémine  
 CH-1680 ROMONT  
 Tel. +41 26 651 92 11  
[Info.switzerland@schoellerallibert.com](mailto:Info.switzerland@schoellerallibert.com)  
[www.ropac-packaging.com](http://www.ropac-packaging.com)

*Note: For pharma or food application the pails should be washed before use. The customer has to check the integrity of the packaging, handling-unit aspect and pail deformation due to transport; these risks should be taken into account by the customer in his risks assessment.*